

# FS-C5015N

A4 COLOUR PRINTER

► print ► copy ► scan ► fax

## COST-EFFECTIVE COLOUR PRINTING ACROSS A NETWORK.

With this compact device, you'll see your investment in colour printing really pay off. It utilises long-life components and ECOSYS technology based on proven Kyocera monochrome devices. The result? Attractive cost-per-page figures and attractive colour output in one.

- 16 pages per minute in A4 colour and b/w
- Time to first page: 16 seconds
- 600 sheets input capacity as standard, upgradeable to 1,100 sheets
- PowerPC 750CXR/400MHz, 128MB RAM
- PCL6, PostScript 3 and PDF direct printing
- USB 2.0 (Hi-Speed) and network connectivity as standard
- Compact design and small footprint
- Long-life components



A 500-sheet paper cassette allows many print runs without having to refill with paper.



The multi-purpose tray offers excellent flexibility.



ECOSYS®



 KYOCERA

# FS-C5015N

## A4 COLOUR PRINTER



ECOSYS devices are designed to minimise both direct costs and indirect costs, such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

### System platform:

The FS-C5015N offers USB and network connectivity as standard and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

### PRESCRIBE IIc:

With the Kyocera page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

### KM-NET for Client/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or optional network connection. KM-NET Viewer is an advanced printer management software tool using the standardised protocol SNMP.

### GENERAL

**Technology:** Kyocera Colour ECOSYS  
**Engine speed:** Max. 16 pages per minute b/w and full colour  
Up to 16 images per minute in duplex mode (optional)  
**Resolution:** 600 x 600 dpi  
Multi-bit technology for optimum colour output  
**Time to first page:** 16 seconds or less  
**Warm-up time:** 80 seconds or less from power on  
**Duty cycle:** Max. 50,000 pages per month (A4), max. average 2,500 per month  
**Power source:** AC 220 ~ 240 V, 50/60 Hz  
**Power consumption:** Printing: 452 W, Stand-by: 173 W, Power-Saving (ECOpower): 16 W  
**Noise (ISO 7779):** Printing: 52 dB(A), Stand-by: 36 dB(A), Power-Saving (ECOpower): Immeasurably Low  
**Dimensions (W x D x H):** 345 x 470 x 385 mm  
**Weight:** Approx. 24 kg with toner containers  
**Certification:** TÜV/GS, CE  
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

**Input capacity:** 500-sheet universal cassette, 60-105g/m<sup>2</sup>, A4, B5, A5, Letter, Custom (148 x 210 – 216 x 356 mm), 100-sheet multi-purpose tray, 60-200g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (70 x 148 – 216 x 297 mm), max. 1,100 sheets  
**Output capacity:** 250-sheet face-down with paper full sensor, face-up output with optional PT-300

### CONTROLLER

**Processor:** PowerPC 750Cxr / 400MHz  
**Memory:** 128MB RAM + ECOMemory, max. 640MB in 1 DDR SDRAM DIMM slot  
**Emulations:** PCL6 (PCL5c/PCL-XL), KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), PDF direct printing  
**Controller language:** PRESCRIBE IIc  
**Fonts:** 80 outline fonts (PCL6: PCL5c/PCL-XL, KPDL 3); 1 bitmap font; 45 types of one-dimensional barcodes, plus 1 type of two-dimensional barcode (PDF-417).  
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 font format  
**Print features:** eMPS – for quick copy, proof and hold, private print, job storage and job management functionality with hard disk

### INTERFACE

**Standard interface:** USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX, KUIO-LV option interface slot  
**Multiple interface connection (MIC):** Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

### CONSUMABLES

**Toner-kit TK-520K:** Microfine toner black for 6,000 pages in accordance with ISO 10561B.  
**Toner-kit TK-520C:** Microfine toner cyan for 4,000 pages in accordance with ISO 10561B.  
**Toner-kit TK-520M:** Microfine toner magenta for 4,000 in accordance with ISO 10561B.  
**Toner-kit TK-520Y:** Microfine toner yellow for 4,000 pages in accordance with ISO 10561B.  
Capacity of starter toner is black 3,000 pages, cyan, magenta, yellow 2,000 pages in accordance with ISO 10561B.

### OPTIONS

#### Paper handling

**PF-60 Paper feeder:** 500-sheet, 60-105g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (148 x 210 – 216 x 356 mm) max. 1 PF-60  
**DU-301 Duplex unit:** Double-sided printing, 60-105g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)  
**PT-300 Paper tray:** Face-up paper output tray for 100 sheets

#### Memory

**Printer memory:** 1 slot (64, 128, 256, 512MB DDR SDRAM DIMM)  
**CompactFlash® card:** 1 slot (up to 2GB) for printing forms, fonts, logos, macro storage  
**Hard disk HD-5:** 40GB HDD for easy document management  
**OCR-2:** Font ROM with OCR-A and OCR-B font types

#### Optional interface

**IB-23 Network card:** 10Base-T/100Base-TX  
**SB-70 Network card:** Wireless LAN – IEEE 802.11b  
**SB-110FX Network card:** 10Base-T/100Base-TX/100Base-FX, FibreOptic  
**SB-110 Network card:** 10Base-T/100Base-TX

### WARRANTY

2-year warranty as standard. Kyocera guarantees the drums and developers for 3-year or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

**KYO LIFE** The up to 3-year on-site warranty extension for printer and options.



### Select your options to suit your needs:

Paper tray (PT-300)

Duplex unit (DU-301)

Paper feeder (PF-60)

Cabinet (CB-60)



Product depicted includes optional extras

### Your Kyocera Business Partner:

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com  
KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

